

## FEATURES – FLEXO WATER COMBI FLW

- Simultaneous processing system of the whole plate surface
- Pre and main exposure with pump and vacuum gauge
- Fastening section on a table with permanent sticky plate and automatic overturning Washout with automatic height adjustment of brushes and with an orbital and alternating movement. Independent movement of the table
- Final cleaning section with one rotating cylindrical brush
- Drying section with 2 independent drawers
- Post-exposure and finishing section with leds informing the state of lamps 9 channel touch screen controller, for each thickness and relief required: pre-exp. Time, main exposure, washout time, quantity of automatic regeneration, post- exp. finishing, 2 times for each of the 2 drawers
- Water and dryer section temperature control
- Detergent doser pump
- Sand filtration system

	<b>27/35</b>	<b>30/40</b>
<b>Exposure size (mm)</b>	700x900	780x1030
<b>Exposure size (inches)</b>	27"x35"	30"x40"
<b>Quantity developer in tank (l)</b>	110	110
<b>UVA exposure lamps</b>	N.16 60W 10R L.1200	N.16 60W 10R L.1200
<b>UVA post-exposure lamps</b>	N.14 60W 10R L.1200	N.14 60W 10R L.1500
<b>UVC lamps</b>	N.13 36W L.1200	N.13 36W L.1200
<b>Maximum thickness processable (mm)</b>	3,94	3,94
<b>Wattage (kW)</b>	15	15
<b>Electrical supply</b>	230V 3PH+GND 60Hz 400V 3PH+N+GND 50Hz	
<b>Overall size (LxWxH) (cm)</b>	290x180x135	290x180x135