

## **FEATURES – GS LINE**

- Black layer removal section.
- Wash-out section.
- Pre-dryer / dryer section.
- Touchscreen controlled.
- Wash-out carried out by 2 orbital floating brushes.
- Post exposure section.
- Transport plate.

Optional:

- Exposer under the tunnel.

	<b>500</b>	<b>700</b>	<b>900</b>
<b>Max plate size (mm)</b>	500	700	900
<b>Max plate size (inches)</b>	19,6"	27,5"	35,4"
<b>UVA lamps (with TUNNEL)</b>	4x40W L. 600	4x60W L. 1200	4x60W L. 1200
<b>Tank capacity (l)</b>	110 liter	110 liter	110 liter
<b>Wattage (kW) machine</b>	12	14	16
<b>1: Machine d'alimentation électrique</b>	230V (3PH+GND) 60Hz 400V (3PH+N+GND) 50Hz		
<b>Wattage (kW) Boiler</b>	26 kw		
<b>1: Electrical Supply Boiler</b>	400V (3PH+GND)		
<b>Washout heater (W)</b>	2x2000	2x2000	2x2000
<b>Dryer heater (kW)</b>	4	6	6
<b>Overall size (LxWxH) (cm)</b>	110x300x117	130x360x120	140x360x129
<b>Weight (kgs)</b>	400	480	700